Model 20A

ECG / Arrhythmia Simulators

Compact and lightweight, our ECG and Arrhythmia simulator is designed to fit your needs, tool case and budget!

Use this simulator to test your patient monitors, telemetry systems and anywhere a quick ECG or Arrhythmia simulation is needed.

The versatile 6-lead configuration provides an additional pre-cordial lead and allows you to check reference leads without the need for a full 12 lead layout.

Model 20A ECG / Arrhythmia Simulator:

ECG Rates: 30, 60, 80, 100, 120, 160, 200, 240 & 300 bpm.

Arrhythmias: PVC1, PVC2, Pair PVC, PVC1 & PVC2 ongoing, Mulifocal PVCs, Ventricular Fibrillation and Asystole.

Model 20A ECG

Features:

- Full multi-lead simulation
- ECG sensitivity of 0.5, 1.0 & 2.0 mV
- 2 Hz Square waveform
- Lead interface: RA, RL, LA, LL, V1, V6
- Battery and ECG lead continuity tests
- 9V battery included

Performance Specifications Model 20A ECG

Normal Sinus Rhythm:

30, 60, 80, 100, 120, 160, 200, 240 and 300 BPM

Arrhythmias:

PVC1, PVC2, Pair PVC, PVC1 & PVC2 ongoing, Multifocal PVCs, Ventricular Fibrillation and Asystole

ECG Performance:

Square Wave: 2 Hz

Amplitudes:

0.5, 1.0 and 2.0 mV

Additional Test Functions:

Lead Continuity Tester Battery Tester

Case

High-impact Plastic

Power:

9 V alkaline battery (included)

Dimensions:

4.25 in L x 2.5 in W x 1.06 in H (10.8 cm L x 6.35 cm W x 2.69 cm H)

Weight:

5.29 oz. (150 g)

All specifications subject to change without notice.



130 - 4020 Viking Way, Richmond BC, Canada V6V 2L4

Phone: 604.291.7747 • Fax: 604.294.2355 Toll-free (North America only): 800.667.6557

Email: customerservice@datrend.com

© DATREND SYSTEMS INC. JULY 2014